



Warewashing Systems

DynaTemp®

Project _____
 Item _____
 Quantity _____
 CSI Section 11400
 Approval _____
 Date _____

DynaTemp®

Models
DynaTemp



Standard Features

- Sani-Sure™ feature assures proper rinse water temperature
- Multi-cycle timer
- Digital controls
- Triple Wash Arm for consistent reliable washing performance
- Self-diagnosing digital controls diagnose most common issues and indicate what the issue is if something happens that affects the operation of the dishwasher
- Specially designed stainless steel nozzles provide superior cleaning action
- 17-1/4" (438 mm) door opening accepts 18" (457 mm) trays
- Interchangeable wash/rinse arms screw out for simple cleanup
- Auto-fill/auto-start
- Door switch
- Delime/manual wash switch
- Vent fan control - shuts vent fan off when machine is idle
- Low watt density electric wash tank heater
- Hi-limit thermostat and low water protection
- Adjustable bullet feet
- Front and side dress panels
- Detergent/rinse additive signal connection fuse box
- Self-draining stainless steel pump
- Interchangeable scrap baskets

Mandatory Specs

- Specify:
- Electric
 - Steam
- Specify voltage _____
- Specify booster size _____

Options

- 480V Electrical
- Single Phase
- 1/2" Pressure Regulator
- Drain Quench System
- Scaltrol
- Water Hammer Arrestor
- Flanged Feet
- Door Interlock
- Steam Booster Heater
- Security Package

Accessories

- 36-Compartment Rack
 - 4-1/8" tall (105 mm)
 - 5-5/8" tall (143 mm)
 - 7" tall (178 mm)
- Combination Rack
- Peg Rack

Specifications

Uses 0.69 gallons (3 liters) of water per rack
 Total automatic (normal) cycle - 58 seconds
 57 racks per hour (normal) cycle
 Built-in 70°F (38.9°C) rise booster heater
 1 hp wash pump motor
 Single point connections for all utilities

Field convertible from straight through to corner and vice versa

Field convertible from 3-phase to single-phase and vice versa

Durable stainless steel construction

Uses standard 20" X 20" (508 mm X 508 mm) racks



Intertek



Intertek



A – DRAIN 1 1/2"
 B – WATER INLET 1/2" NPT
 C – ELECTRICAL CONNECTION
 D – STEAM INLET
 E – STEAM OUTLET

All dimensions from the floor can be increased 2" using the machine's adjustable feet.

MODEL NO.	MACHINE DIMENSIONS				DRAIN HEIGHT	SHIPPING INFORMATION					
	HEIGHT	WIDTH	WIDTH BETWEEN TABLES	DEPTH		WEIGHT	CLASS	CUBE	HEIGHT	WIDTH	DEPTH
DynaTemp	61" (1549 mm)	30-5/16" (770 mm)	25-5/16" (643 mm)	29-1/2" (749 mm)	14-1/2" (368 mm)	366 lbs (166 kg)	150	53.34 cu. ft.	66.5" (1690 mm)	33" (839 mm)	42" (1067 mm)

DIMENSION REQUIREMENTS	
Wall Clearance - Rear (minimum)	1-1/4" (32 mm)
Wall Clearance - Corner Installation Side (minimum)	6-1/4" (159 mm)
Standard Table Height	34" (864 mm)
Inside Clearance	17-1/4" (438 mm)
Machine Height with Door Open	81" (2057 mm)

STEAM REQUIREMENTS	
Steam Flow Pressure (PSIG)	15-20
Consumption @ 15 PSIG (lbs/hr)	45

WATER REQUIREMENTS	
Inlet Temperature	
70°F (38.9°C) Rise	110°F (43°C)
No Booster	180°F (82°C)
Gallons per Hour	39.5 gal (149.5L)
Gallons per Rack	.69 gal (2.6 L)
Waterline Size IPS (minimum)	1/2"
Drainline Size IPS (minimum)	1- 1/2"
Flow Pressure (PSI)	8
Wash Tank Capacity	8 gal (30 L)
Booster Tank Capacity	3 gal (11 L)

OPERATING CAPACITY				
Racks per Hour		Normal 57	Heavy 32	Extra Heavy 15
OPERATING CYCLE (seconds)	Wash	Rinse	Dwell	Total Cycle
Normal	40	11	7	58
Heavy	90	11	7	108
Extra Heavy	220	11	7	238

OPERATING TEMPERATURES	
Wash (minimum)	150° F (66° C)
Rinse (minimum)	180° F (82° C)

WASH PUMP MOTOR		
Wash Pump Motor Horsepower		1 HP
	Volts	KW
Electric Wash Tank Heater	208V	4.1
	230V	5.0
	460V	5.0
Electric Rinse Tank Heater - 70°F (38.9°C) Rise	208V	10.5
	230V	12.9
	460V	12.9

APPROXIMATE LOAD AMPS			
	No Booster	70°F (38.9°C) Rise	Steam
Power Supply	AMPS	AMPS	AMPS
208V/60HZ/1PH	24.6	75.8	6A
208V/60HZ/3PH	16.3	46.3	6A
230V/60HZ/1PH	26.6	83.6	6A
230V/60HZ/3PH	17.5	50.7	6A
460V/60HZ/3PH	7.9	24.1	N/A

HOW TO SPECIFY: DynaTemp

Jackson WWS, Inc.

Shipping Address: 6209 North U.S. Highway 25E, Gray, KY 40734

Mailing Address: P.O.Box 1060, Barbourville, KY 40906

Telephone: 888-800-5672 • Fax: 606-523-1799

Email: info@jacksonwws.com

07610-004-32-38 [10/03/17]

www.jacksonwws.com