

DynaStar®

High Temperature Sanitizing Door-type Dishwasher

- Built-in booster heater with exclusive Sani-Sure[™] final rinse system ensures proper rinse temperature
- Adjustable rinse system Econo or Turbo
- Pumped rinse for consistent rinse pressure
- Door-actuated start
- Three (3) selectable timed cycles for warewashing flexibility and performance
- Solid-state controls feature a digital LED display and onboard service diagnostics
- Delime cycle
- Triple wash arm for consistent, reliable washing performance
- Specially designed stainless steel nozzles provide superior cleaning action
- Full wrap handle is ideal for both pass thru and corner installations
- Field convertible from straight-through to corner and vice versa (kit required)
- Field convertible from 3-phase to single phase and vice versa (kit required)
- Powerful 1 HP stainless steel pump motor













DynaStar®

Cleanability

Our triple wash arm is engineered to focus more water on the dishes for superior cleaning performance. Our adjustable rinse system keeps you in control - choose Econo or Turbo based on the soil level of each load.

Operation

Easy-to-read digital controls, a full wrap tubular handle, and a door-activated drain closure make operation of the DynaStar a breeze.

Serviceability

Ease of serviceability is important to Jackson, so the DynaStar was designed to make service access easy. All service parts can be accessed while the unit is in place - no need to pull it from the wall or disconnect tables.









Triple Wash Arm



Interchangeable Scrap Baskets

OPERATING CYCLE TIMES (Seconds) | OPERATING CAPACITY (Racks per Hour)

OPERATING CYCLE	CYCLE TIME	RACKS PER HOUR	GALLONS PER HOUR
Normal	:58	62	43.40
Heavy	:108	33	23.10
Extra Heavy	:238	15	10.50

Contact Jackson -

JAC-SS-0011 [02/09/22]

Address

6209 N U.S. Highway 25E Gray, Kentucky 40734 **Telephone & Fax** T 888.800.5672 F 606.523.1799 Email

customer.service@jacksonwws.com





JACKSON WAREWASHING SYSTEMS

