



Warewashing Systems

We've got your high temperature door-type dishmachine.

No matter what you're looking for in a high temperature sanitizing door-type unit, Jackson offers a variety of solutions, with a full range of units that deliver premium quality, superior performance and outstanding value.

GOOD

NXP-HTD[®]



- Fresh water rinse
- Single cycle
- Delime cycle

BETTER

TEMPSTAR[®]



- Fresh water rinse
- Four selectable cycles
- Front dress panel
- Delime mode
- Tall chamber available
- Ventless with Energy Recovery available

BEST

DYNASTAR[®]



- Fresh water rinse
- Three selectable cycles
- Front and side dress panels
- Digital LED display with service diagnostics
- Adjustable rinse - Econo or Turbo
- Triple wash arm
- Delime cycle
- Ventless with Energy Recovery available

Jackson®

Warewashing Systems



Spec/Feature	NXP-HTD®	TEMPSTAR®	DYNASTAR®
Gallons per Rack	0.89	0.89	0.66
Racks per Hour	63 (58)*	63 (58)*	62 (57)*
Cycle Time (seconds)	57	57 (Normal)	58 (Normal)
Operating Cycles	1	4	3
Built-in Booster	70 °F rise	40 or 70 °F rise	40-70 °F rise
Water Inlet Temperature	110 °F minimum	110 or 140 °F minimum	110 °F minimum
Temperature Display	Digital	Dial	Digital
Controls	Digital	Analog	Digital w/service diagnostics
Door Interlock	Not Available	Optional	Standard
Wash Arms	1 Upper & 1 Lower	1 Lower & 1 Upper	Triple Wash Arms
Rinse	Sani-Sure™ fresh water rinse	Sani-Sure™ fresh water rinse	Sani-Sure™ pumped fresh water rinse
Scrap Baskets	Single - large	Single - large	Two interchangeable
Electrical Connection	Single point	Single point	Single point
Field Convertible from Straight-thru to Corner and Vice Versa	Standard, optional kit required	Standard, optional kit required	Standard, optional kit required
Field Convertible from 3-phase to single phase	Standard, optional kit required	Standard, optional kit required	Standard, optional kit required
Electrical	208-230/60/1 208-230/60/3	208-230/60/1 208-230/60/3 460/60/3 (upcharge)	208-230/60/1 208-230/60/3 460/60/3 (upcharge)
Vent Fan Control	Standard	Standard	Standard
Delime	Cycle	Mode	Cycle
Dress Panels	None	Front only	Front & sides
Security Package	Not Available	Optional	Optional
Tall Chamber	Not Available	Optional	Not Available at this Time
Ventless with Energy Recovery	Not Available	Optional	Optional
Tall Chamber, Ventless with Energy Recovery	Not Available	Optional	Not Available at this Time

*Racks per hour calculated with NSF suggested load time of five (5) seconds for door-types (straight-thru)