

We've got your high temp undercounter dishmachine.

No matter what you're looking for in a high temperature sanitizing undercounter, Jackson's got you covered. We offer a variety of solutions, with a full range of units that deliver premium quality, superior performance and outstanding value.



- SEER units additional features
 - Steam elimination
 - Energy recovery
 - Service diagostics





Warewashing Systems

98 2 **2** 2 u _____u GOOD BETTER BEST BEST NXP-HTU **DISHSTAR® HT-E DISHSTAR® HT-E-SEER DISHSTAR® HT** Gallons per Rack 0.83 1.10 0.60 0.60 Racks per Hour 30 (24)* 30 (24)* 36 (27)* 24 (20)* Cycle Time (seconds) 120 (Normal) 120 (Normal) 100 (Normal) 145 (Normal) Wash Design Fill and Dump Recirculating Recirulating Recirculating **Operating Cycles** 2 3 3 3 Sani-Sure[™] Final Standard Standard Standard Standard **Rinse System** Water Inlet 110 °F 110 °F 110 °F 40-90 °F Temperature Temperature Display Digital Digital Digital Digital Door Interlock Not Available Not Available Not Available Standard Sani-Sure™ fresh Sani-Sure™ fresh Sani-Sure[™] fresh Sani-Sure[™] fresh Rinse water rinse water rinse water rinse water rinse Scrap Baskets Above water Above water Above water Above water 208-230/60/1 208-230/60/1 Electrical 208-230/60/1 208-230/60/1 460/60/3 (upcharge) 460/60/3 (upcharge) **Delime Cycle** Standard Standard Standard Standard **Built-in Chemical** Standard Standard Standard Standard Pumps Auto Prime Standard Standard Standard Standard Standard Pumped Drain Standard Standard Standard Double-wall No Yes Yes Yes Construction Steam Elimination Not Available Not Available Not Available Standard

*Racks per hour calculated with NSF suggested load time of thirty (30) seconds for front opening dishmachines.

Contact Jackson

and Energy Recovery

Address

6209 N U.S. Highway 25E Gray, Kentucky 40734 **Telephone & Fax** T 888.800.5672 F 606.523.1799

Email customer.service@jacksonwws.com



in JACKSON WWS

JAC-SS-0019 [01/18/23]

JACKSON WAREWASHING SYSTEMS